

Intrusion



Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Passive Infrared Detectors			
<i>Classic</i>			
Honeywell	IS215TCE Passive Infrared Detector range 12x12m, intelligent temperature compensation, digital signal processing	IS215TCE	
Honeywell	IS220T Passive Infrared Detector range 15x21m or 10x15m, remote controlled LED, variable installation height (1.2 – 3.0m), temperature compensation	IS220T	
Honeywell	IS216T-CUR Curtain Passive Infrared Detector range 10m, intelligent temperature compensation, digital signal processing	IS216TCUR	
Honeywell	IS2560T Passive Infrared Detector range 17x21m, sensitivity adjustable in 4 steps, intelligent temperature compensation, digital signal processing	IS2560T	
Honeywell	IS2560TC Passive Infrared Detector range 17x21m, sensitivity adjustable in 4 steps, remote controlled LED, cover and wall tamper contacts, changeover alarm relay, intelligent temperature compensation, digital signal processing	IS2560TC	
Honeywell	IS25100TC Passive Infrared Detector range 25x5m, sensitivity adjustable in 4 steps, remote controlled LED, cover and wall tamper contacts, changeover alarm relay, intelligent temperature compensation, digital signal processing	IS25100TC	
	RX40QZ-BE Quad PIR Detector range 12x12m, temperature compensated, 9.5-16VDC	RX40QZBE	
	FX40BE PIR Detector with lookdown zone, range 12x12m, temperature compensated, 9.5-16VDC	FX40BE	
	FX40D-BE PIR Detector double-shielding, with lookdown zone, range 12x12m, temperature compensated, 9.5-16VDC	FX40DBE	
	CX502BE Quad PIR Detector with lookdown zone, range 15x15m, temperature compensated, 9-18VDC	CX502BE	
	CX702-V PIR Detector double-shielding, with lookdown zone, range 21x21m, temperature compensated, 6-18VDC	CX702V	
	RK410RQ Zodiac Quad PIR Detector range 12x12m, with mounting base, temperature compensated	RK-RK410RQ	
	NEXT PIR Detector range 12x12m	VS-01029B	

Version 2.0 May 2006. ADI is a tradename of Honeywell Security B.V.

Intrusion



Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Passive Infrared Detectors			
Pet Immune			
	IS2535T PIR Detector Pet Immune range 11x12m, pet immunity adjustable: 0, 18 of 36 Kg, sensitivity adjustable in 4 steps, inclusive pet immunity lens and high security lens, intelligent temperature compensation, digital signal processing	IS2535T	
	IS2535TC PIR Detector Pet Immune range 11x12m, pet immunity adjustable: 0, 18 of 36 Kg, sensitivity adjustable in 4 steps, remote controlled LED, cover and wall tamper contacts, changeover alarm relay, inclusive pet immunity lens and high security lens, intelligent temperature compensation, digital signal processing	IS2535TC	
	IS2260T PIR Detector Pet Immune range 18x36m, pet immunity up to 18 kg, ASIC signal processing, ultra-low power consumption (<4mA), quiet relay	IS2260T	
	NEXT K9-85 PIR Detector pet-friendly, range 12x12m	VS-012740	
	RK410PT Zodiac Digital PIR Detector pet-friendly, range 12x12m, temperature compensated	RK410PT	
Anti-Mask			
	CX502AM-PLUSBE Anti-Mask PIR Detector with lockdown zone, range 15x15m, temperature compensated, 9-18VDC	CX502AMPLUSBE	
	iWise G3 Quad-PIR Anti-Mask range 15m, with lockdown zone, LED walk test, complies with EN50131-1 Grade 3, 9-16VDC	RK800Q0G3BLA	
Ceiling mount			
	SX360ZV PIR Detector 360° with lockdown zone, range 18m, temperature compensated	SX360ZV	
	RK200DPC LuNAR PIR Detector 360° ceiling mount, range 13m, max. height 4m	RK2000DPC	
	PA6812 PIR Detector ceiling mount, range 12x12m at 90°, height 2 - 5m	PA6812	
	PA6820 PIR Detector ceiling mount, range 20x1m at 6°, height 2 - 5m	PA6820	

Intrusion

















Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Passive Infrared Detectors			
Ceiling mount			
	PA6805 PIR Detector ceiling mount, range 4m at 360°, height 2 - 5m	PA6805	
	PA6810 PIR Detector ceiling mount, range 15m at 360°, height 2- 5m	PA6810	
Outdoor			
	WatchOut PIR Detector range 12m (90°) or 23m (5°), pet immune, two PIR channels, IP65 protection, 9-16VDC, ProSYS compatible	RK312PR0000A	
	VX402 Outdoor PIR Detector range 12x12m, for dual layer detection, temperature compensated, 9.5-18VDC	VX402	
	BX80N Outdoor PIR Detector range 2x12m, for wall and fence detection, temperature compensated, 10-28VDC	BX80N	
	D-ECT2 External Quad-PIR Detector two sets of volt free programmable contacts, IP55 rated, 8 to 30 meter, fully remotely adjustable, outputs also for GJD lighting systems	GJD300	
	LRP4010S Redwall External PIR Detector range 40x10m, 16 zones, 12VDC	LRP4010S	
	LRP404S Redwall External PIR Detector range 40x4m, 16 zones, 12VDC	LRP404	
	LRP3020S Redwall External PIR Detector range 30x20m, 48 zones, 12VDC	LRP3020S	
	LRP100Q Redwall External PIR Detector range 100x3m, 20 zones, 12VDC	LRP100Q	
	LRP5030 Redwall External PIR Detector range 50x30m, 78 zones, 12VDC	LRP5030	
	OPAL XL 12V PIR Detector IP55 rated, 10 to 35 meter, 90 degree fully adjustable	GJD020	
	ELITE 12V PIR Detector white, two sets of volt free programmable contacts, IP55 rated, 10 to 35 meter, 90 degree fully adjustable	GJD023	

Intrusion



Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Passive Infrared Detectors			
Outdoor			
	OPAL RFX Wireless PIR IP55 rated, 10 to 35 meter, 90 degree fully adjustable	GJD018	
Other			
	ACTIV8 PIR with Mono Camera and Microphone range 18x18m, pet immune, camera sensitivity 0.5 Lux, AGC, 420 TVL, built-in microphone with regulation, power consumption 115 mA, adjustable alarm duration (2-240 s), inclusive wall/ceiling bracket	8IR120	
	ACTIV8 PIR with Color Camera an Microphone range 18x18m, pet immune, camera sensitivity 0.5 Lux, AGC, 380 TVL, built-in microphone with regulation, power consumption 150 mA, adjustable alarm duration (2-240 s), inclusive wall/ceiling bracket	8IR125	
Accessories			
Honeywell	SMB10 Wall bracket per 5 pcs	SMB10	
Honeywell	SMB10C Ceiling mount bracket for SMB10 per 5 pcs	SMB10C	
Honeywell	SMB10T Wall bracket with Tamper per 5 pcs	SMB10T	
	FA-3 Bracket for Wall and Ceiling Mount for RX-40QZ, FX-40 CX-502, MX-40, DX-40 and DX-60 series	FA3	
	CA1W Wall Bracket for CX-702BE	CA1W	
	CA2C Ceiling Bracket for CX-702BE	CA2C	
	FL60N Long beam / Curtain Lens for RX-40QZ and FX-40, range 18x1.8m, angle 10°, 20 detection zones	FL60N	
	CL80 Long beam / Curtain Lens for CX-502, range 24x2.3m, angle 6°, 22 detection zones	CL80	

Intrusion



Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Passive Infrared Detectors			
Accessories			
	LRP105 Redwall Interswitch switching contact 240VAC/1200W, with photosensor, alarm output and remote input	LRP105	
	LRP103DS Redwall Daylight Sensor for Interswitch LRP105	LRP103DS	
	LRP1020 Redwall Walk Tester for adjustment of Redwall detectors	LRP1020	
	SCA Redwall Mounting Bracket for pole mount (48mm)	LRPSCA	
	BWC-401 Bracket for Wall Mount	PU-BWC401	
	BR-1 Mounting Bracket wall mount	VS-017810	
	BR-2 Mounting Bracket corner mount	VS-017820	
	BR-3 Mounting Bracket ceiling mount	VS-017830	
	D-TECT Infra-Red remote programmer key fob	GJD303	
	D-TECT Conduit Cable Entry Adaptor Ring	GJD304	
	D-TECT Pole Mount Clamp	GJD305	
	SAPPHIRE Mk3 - 1500 watt, 230 volt single zone controller	GJD005	
	EMERALD Mk3 - 2 X 1500 watt, 230 volt two zone controller	GJD010	

Intrusion



Please check if products are available in your country before you place your order

Vendor	Description	Product code	
Passive Infrared Detectors			
Accessories			
	2 ZONE SOLITAIRE TOUCH CONTROL 12V, requires one x 230 volt expansion unit	GJD011	
	4 ZONE SOLITAIRE TOUCH CONTROL 12V, requires two x 230 volt expansion units	GJD014	
	SOLITAIRE EXPANSION UNIT, 230 volt unit	GJD012	
	MULTISWITCH 3000, Dusk to dawn or alarm activated light switch. 2x1500w IP65	GJD060	
	HYLITE NIGHT OWL (PHOTO CELL), Dusk to dawn photocell controller	HYL001	
	RFX-3 RECEIVER IP65 rated, weatherproof 3-channel receiver, 150 meters line of sight, 3 volt free contacts	GJD017	
	MULTISPEECH 4 4 Channel 90 second record / playback voice enunciator module	GJD090	
	WEATHERPROOF IP65 TAMPER BOX	GJD190	